

PANEL GUIDE

Honeywell Galaxy Classic – Dial Capture

Updated March 26, 2025

Latest information

<https://www.csl-group.com/panel-guides/honeywell/honeywell-galaxy-classic-range/>

Panel Connection – Dial Capture

Manufacturer	Honeywell
Model	Galaxy Classic Range
Minimum Panel Firmware	4.5 and above
Cable required?	MCM connected to: - DualCom Pro 1 – MCM plug-on module CS.1.402 - DualCom Pro 2 – DI & AL
Panel Profile	Honeywell-Galaxy-MCM
Panel Connection	Dial Capture

DualCom Pro to Panel Wiring

DualCom Pro 1 – MCM plug-on module – Line A DualCom Pro 2 – DI	PSTN A
DualCom Pro 1 – MCM plug-on module – Line B DualCom Pro 2 – AL	PSTN B

Panel Configuration

- Enter Engineering Mode – Menu 56
- Select Internal Telecoms (Option 1)
- Select Format (Option 1)
- Enter SIA (Option 2)
- Select SIA level 3
- Turn on reporting triggers as needed (recommend 10 and 18)
- Select Tel No.1 (option 2)
- Set a dummy phone number, for example 01234 567890
- Select Account Number (option 3)
- Enter ARC Connection ID – see My Base
- Go to Remote Access (Option 12)
- Select Access Period – 4 Anytime
- Select Mode 1 – Direct Access
- Escape to return to Engineering Mode
- Exit Engineer Mode into Day Mode